

Select your barrier here	Maximum free passage And/Or Height of the obstacle	Opening or Closing time Passages/ minutes (TRS)	Arm type						Main features				Communication			
			Standard	Fibre glass	Semi-reinforced	Reinforced	Articulated	Carbon fiber	Fenced	Automatic lifting	Mechanical locking	Swing-off	Re-hinging	TCP/IP	Modbus	XML/RPC
TOLL																
TollPlus 160	4 m	1,2 - 3 s	•					•*		•	•		•*	•*	•*	•*
TollPlus 260	4 m	0,7 - 2 s	•					•		•	•*		•			
TollPlus 262	4 m	0,6 - 2,5 s	•					•*		•	•*		•	•		•*
BL 229 Toll	3 m	0,6 - 2,5 s	•					•*		•	•	•*	•*	•*	•*	
PARKING																
ParkPlus 100	4 m	1,2 - 3 s	•							•	•*		•*	•*	•*	•*
ParkPlus 101	4 m	1,2 - 3 s	•			•				•	•*		•*	•*	•*	•*
BL 229	6 m	1 - 4 s	•					•*		•	•	•*	•*	•*	•*	
ParkPlus 244	4 m	1,2 - 3 s			•			•*		•			•	•		•*
BL 44	4 m	2 - 3 s			•					•	•*		•*	•*	•*	•*
TRAFFIC MANAGEMENT																
BP 56	8 m	9 s				•					•					
BL 45A	12 m	8 s	•								•*		•*	•*	•*	
BL 45F	10 m	8 s		•							•*		•*	•*	•*	
BL 45T	12 m	8 s		•									•*	•*	•*	
BL 52	14 m	8 - 12 s	•							•*	•					
BL 77	14 m	10 - 24 s		•							•					
RISING FENCED BARRIERS																
BL 46	7 m x 1,8 m		•							•	•*	•*		•*	•*	•*
BL 47	3,35 m x 2 m / 4,35 m x 2 m	5 - 8 s				•				•	•*	•*		•*	•*	•*
BLG 76 H/L	4,4 m x 2,3 m / 5 m x 1,9 m	8 - 12 s	•							•	•					
BLG 77 H/M	4,88 m x 3,46 m / 4,88 m x 2,24 m	7 - 10 s				•				•	•					
BLG 77 HL/L	6,15 m x 2,85 m / 6,15 m x 2,24 m	7 - 10 s				•				•	•					
PERIMETER ACCESS																
BL 10	8 m	Manuel	•													
BL 15	4 m	1,2 - 3 s	•					•*		•	•*		•*	•*	•*	•*
BL 227	6 m	1,5 - 3,5 s	•					•*		•*	•*	•*	•	•		
BL 229	6 m	1 - 4 s	•					•*		•*	•	•*	•*	•*	•*	
BL 40	8 m	3,5 - 8 s	•							•*	•*	•*		•*	•*	•*
BL 41	12 m	3,5 - 8 s	•							•*	•*	•*		•*	•*	•*
BL 43	6 m	3,5 - 8 s				•				•*	•*	•*		•*	•*	•*
BL 52	14 m	8 - 12 s	•							•*	•					
BL 53	8 m	5 - 10 s				•					•					

Legend: * optional

Technical data are not contractual