





Access Controlled... Future Secure

Pedestrian

SClearLock

Automatic Systems' ClearLock security doors are cylindrical booths that ensure strict entrance control and are especially designed for sensitive sites. Combining high security and elegance, the ClearLock series is available in different sizes, shapes and finishes, with single or double doors both on entry and exit.

CLEARLOCK 636

Passage width: 27 1/2" (700 mm) External diameter: Ø 45 1/4" (1150) H: 92 1/2" (2350 mm)



Security & Safety

- Full-height circular booth with sliding entrance and exit doors that never open simultaneously
- Bullet, vandalism and burglary resistant, compliant with industry standards (EN 1063, EN356, UL752...)

Aesthetics & Customization

- Elegant design with large glass surface
- Doors mounted directly onto existing floor
- Compact footprint
- Round or square frame
- Wide range of finishes (stainless steel, painted...)

Adaptability & Flexibility

- Products available disassembled, in accordance with on-site installation requirements
- Electronic and mechanical parts located in the canopy, easily accessible for maintenance
- Numerous accessories available

Reliability & Performance

- Double entrance and exit doors, ensuring fluid throughput (ClearLock 656)
- Control panel for set up and management
- Remote management using TCP/IP connectivity

CLEARLOCK 646

Passage width: 27 1/2" (700 mm) Footprint: L: 45 1/4" (1150 mm) W: 45 1/4" (1150 mm) H: 92 3/4" (2360 mm)



CLEARLOCK 656

Passage width: 35 1/2" (900 mm) Footprint: L: 58 1/2" (1485 mm) W: 74 3/4" (1900 mm) H: 94 1/2" (2400 mm)



Standard Ral Colors



All other finishes must be specified when ordering.



1-800-263-6548 www.automatic-systems.com

