

Datasheet NAM-SLIM EP-DS-EN-C

Options

- 1. For convenient reader integration, we offer two plexi locations: top and/or front facing
- Slotted plexi for Barcode cards 2.



- Increased space for multiple integrations З. a. Industrial PC integration
 - b. Elevator display screen
 - Angled housing for elevator display C. * Max. dimensions : 4 x 7 x 2 in (102 x 178 x 50.8 mm)



OPT







The information contained in this document is the property of Automatic Systems and is confidential. The recipient shall refrain from using it for any purpose other than the use of the products or the execution of the project to which it refers and from communicating it to third parties without written prior agreement of Automatic Systems. Document subject to change without notice.





The SlimLane EP swing door security entrance lane offers a high bidirectional throughput and uncompromising security.

With its transparent, elegant design, the SlimLane EP is designed to integrate perfectly into any architectural environment while allowing the integration of multiple peripherals

Equipped with a high processing capacity and an exclusive detection system, the SlimLane EP guarantees accurate user tracking and prevents any unauthorized access.

The SlimLane EP is a modular product that can be installed as a single lane or in a multi-lane array.

The SlimLane EP option is only available on short cabinets.

For standard information, please refer to the SlimLane Datasheet (NAM-SLIM 940-DS-EN)

STANDARD DIMENSIONS (inches / mm)



www.automatic-systems.com